Item No.: WS-011 Driver unit: Ф10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm

Item No.: WS-013 Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm

Item No.: WS-015
Driver unit: ⊕10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance: 16  $\Omega$ Rated power: 100Mw Cable length: 120Cm Plug type: 3.5mm







Item No.: WS-012
Driver unit:  $\Phi$  10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm

Item No.: WS-014
Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance: 16  $\Omega$ Rated power: 100Mw Cable length: 120Cm Plug type: 3.5mm

Item No.: WS-016
Driver unit:  $\Phi$  10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm







Item No.: WS-018
Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm




Item No.: WS-020 Driver unit: ⊕10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \, \Omega$ Rated power:  $100 \, \text{Mw}$ Cable length:  $120 \, \text{Cm}$ Plug type:  $3.5 \, \text{mm}$ 



Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm





Item No.: WS-019
Driver unit: Φ10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm



Item No.: WS-022 Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm



Item No.: WS-025 Driver unit:  $\Phi$ 10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm



Item No.: WS-028
Driver unit: ⊕10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \, \Omega$ Rated power:  $100 \, \text{Mw}$ Cable length:  $120 \, \text{Cm}$ Plug type:  $3.5 \, \text{mm}$ 

Item No.: WS-033 Driver unit: ⊕10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm

Item No.: WS-038
Driver unit: ⊕10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm








Item No.: WS-030
Driver unit: Φ10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm



Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm

Item No.: WS-039
Driver unit: Φ10mm

Frequency response: 20-20,000HZ

Sensitivity: 107db at 1KHZ

Impedance:  $16 \Omega$ Rated power: 100 MwCable length: 120 CmPlug type: 3.5 mm





